Declaration of Performance No: G 23 01

- 1. Unique product identification code: GARJDxxx
 - Type, series or other product identification code enabling unique identification: glazed ceramic tile element with an absorbing power of $0.5\% < E \le 3.0\%$.
- 2. <u>Intended use:</u> The product group comprises glazed tile elements for finishing of internal and external walls in areas that may be subjected to the effects of frost. The range of colours is diverse, with various types of décor in a natural variation of tints, which are marked on the packaging in the column titled "Tint". Before installing the product, pay attention to the information provided on the packaging, in the accompanying leaflets and in the manufacturer's technical catalogue (https://www.rako.cz/cs/pro-odborniky). Observe the rules provided in the relevant manuals for applying construction chemicals.
- 3. <u>Manufacturer:</u> LASSELSBERGER, s.r.o., Adelova 2549/1, 320 00 Plzeň-Jižní Předměstí (Company ID No: 25238078) Czech Republic, Phone: +420 800 303 333, Fax: +420 378 021 119, Email: info@rako.cz
- 4. Authorised representative: N/A
- 5. <u>Systems for assessing and verifying the performance stability of construction products:</u> System 4 (according to Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 and Annexes V, point 1.5 of 27 May 2014).
- 6. In the case of the declaration of performance concerning construction products subject to the <u>harmonized standard</u> EN 14 411: 2012: name and identification number of notified body: N/A.
- 7. The performances declared in the statement apply to all commercial quality classes:

Table 1: Declared product performances

rabic 1. Beclarea product per		
Basic characteristics	Value of properties	Harmonized technical specification
Reaction to fire	Class A1 _{fl} /A1	without testing (decree 96/603
		EHS)
Fracture load	min. 900 N	
Durability for:		
- internal use	compliant	
- exterior use: freezing - thawing	compliant	
Resistance against sudden	compliant	
changes of temperature		
Adhesion	- with bonding cement type C2:≥1.0 N/mm ²	EN 14 411: 2012
Hazardous substance release		1
- cadmium	max. 0.07 mg/dm ²	
- lead	max. 0.8 mg/dm ²	
Assessment of natural	max. index of mass activity 1.0	
radionuclide content		
		Act No 263/2016 Coll., and
		Implementing Decree No 422/2016
		Coll. Section 102, as amended

^{*}NPD (No Performance Determined)

The products comply with the requirements for the content of natural radionuclides according to Decree No. 422/2016 Coll., as amended. The products further comply with the requirements for leachability of Cd and Pb within the meaning of EN 14 411: 2012, and can be used on worktops and wall surfaces where food is prepared and where food comes into direct contact with the glazed surface of the tile element.

8. Relevant technical documentation and/or specific technical documentation:

This declaration of performance complies with Regulation (EU) No. 305/2011 issued at the exclusive responsibility of the above-specified manufacturer. The performances of the above-specified product comply with the set of declared performances. According to Regulation REACH No 1907/2006, the ceramic tile elements are objects that do not emit any chemical substances.

Signed on behalf of the manufacturer: 9 April 2024 in Plzeň

LASSELSBERGER, s.r.o.

Adelova 2549/1, 320 00 Plzeň-Jižní Předměstí IČ: 25238078, DIČ: CZ25238078

RNDr. Eva Dvořáčková, Ph.D., Quality Manager